

GOLEM

Automatic wall-mounted flushing device with infrared sensor

FEATURES

The flusher is designed for urinals with internal water supply H843061, H840201, H844100. It reacts to the presence of a person in front of the urinal at a distance of max. 0.7 m from the sensor for a period longer than 7.5 s. Flushing occurs after the person leaves the sensing zone. Flushing time is adjustable from 0.5 to 15.5 s. Flushing time setting and switch-off option, sensors using remote control H894078. Sensor switch-off function, automatic flushing after 24 hours from the last valve closing. Water flow control by ball valve. Battery status monitoring. The product contains a chrome-plated brass body with electronics, valve, supply battery, ball valve and screw connection, inlet pipe with rubber seal and chrome-plated cover.

Adjustable flushing time

Application place: **Urinal**

Finish: **Chrome**

Flow rate (l/min - 3 bar): **20**

Installation type: **Wall-mounted**

Maximum flushing time (s): **0.5**

Minimum flushing time (s): **15.5**

Operating voltage (V): **9**

Water connection thread: **1/2"**

© Copyright 2026, JIKA - Všechna práva vyhrazena, S.A. - All rights reserved | 20-11-2026 | http://www.jika.eu/products/automatic-wall-mounted-flushing-device-infrared-sensor-H8948270000001?sku=H8948270000001

COMPATIBLE WITH



Siphonic urinal

H8402010000001



Siphonic urinal, outer water inlet

H8430610000001

Universal remote control

H8940780000001

Golem

The JIKA brand assortment includes a range of high-quality ceramic products for building technical rooms, including the complete Golem urinal series.



© Copyright 2026, JIKA - Všechna práva vyhrazena, S.A. - All rights reserved | 20-11-2026 | http://www.jika.eu/products/automatic-wall-mounted-flushing-device-infrared-sensor-H8948270000001?sku=H8948270000001