

A LAUFEN GROUP COMPANY DECLARATION OF CONFORMITY

according to Directive 2006/95/EC of the Europian Parliament and of the Council of 12 December 2006

We, the LAUFEN CZ, s.r.o. V Tůních 3/1637, 120 00 Praha 2 Czech Republic

declare in exclusive responsibility the conformity of lights and mirror cabinets with lights with requirements defined by EN 60 598-1ed4:2005 and EN 60598-2-1:1997. Protection class (IP class) was checked and defined for all products mentioned below and products are marked with

C€ marking.

Product Nr.:	set name:	Product descriprion:
H47J7300200001	light GEMMA 280	LED, IP44, 1×6W, 840 lm, 280×112×14 mm, with Multisystem adapter
H47J7301200001	light GEMMA 490	LED, IP44, 1×6W, 840 lm, 494×112×14 mm, with Multisystem adapter
H47J7304200001	light ELLA 300	LED, IP44, 1×6W, 600 lm, 300×80×80 mm, with Multisystem adapter
H47J7305200001	light ELLA 500	LED, IP44, 1×6W, 745 lm, 500×80×80 mm, with Multisystem adapter
H47J7307200001	light ABI 300	LED, IP44, 1×6W, 598 lm, 300×130×70 mm, with Multisystem adapter
H47J7303200001	light Moonbox New	LED, IP 44, 1x8W, 510 lm, 300x25x83mm with Multisystem adapter

Product Nr.:	set name:	Product descriprion:	
H4943020390001	double Sunrise lighting for Lyra	IP 44, 2x G9,max 33 W	
H47J7302200001	Horizon New	LED, IP 44, 1×6W, 390Im, 233×42×85 mm	
Mirror with integrated LED lighting			
H4557051731441	mirror Clear	mirror with LED lighting, IP44, without switch, for connection 230 V, bevell 5 mm, with possibility demister foil max. 574 x 274 mm, 45X81cm	
H4557151731441	mirror Clear	mirror with LED lighting, IP44, without switch, for connection 230 V, bevell 5 mm, with possibility demister foil max. 574 × 274 mm, 55X81cm	
H4557251731441	mirror Clear	mirror with LED lighting, IP44, without switch, for connection 230 V, bevell 5 mm, with possibility demister foil max. 574 x 274 mm, 60X81cm	
H4557351731441	mirror Clear	mirror with LED lighting, IP44, without switch, for connection 230 V, bevell 5 mm, with possibility demister foil max. 574×274 mm, $70X81$ cm	
H4557651731441	mirror Clear	mirror with LED lighting, IP44, without switch, for connection 230 V, bevell 5 mm, with possibility	

In Prague

12nd April 2018

Ing. Michal Kašpar

Quality manager

fop mobile

demister foil max. 574 x 274 mm, 100X81cm