

DECLARATION OF PERFORMANCE

DoP No 997

1. Unique identification code of the product-type:

For product number please see attached list

Product-Type, batch or serial number or any other element allowing identification of the construction product

WP: Wallhung WC-pan(s) made of sanitary ceramics

WCS: Wallhung close-coupled suite(s) made of sanitary ceramics

PP: Pedestal WC-pan(s) made of sanitary ceramics

PCS: Pedestal close-coupled suite(s) made of sanitary ceramics

PO: Pedestal onepiece WC(s) made of sanitary ceramics

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Personal hygiene (PH)

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

LAUFEN CZ, spol. s r. o.

V Tůnách 3/1637

120 00 Praha 2, Česká republika

Tel: +420 296 337 711 / e-mail: office.praha@cz.laufen.com / website: www.jika.cz

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

5. System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Construction Products Regulation (EU) 305/2011, Annex V:

System 4

6. Harmonised standard:

EN 997: 2012 + A1: 2015

7. Declared performance

Essential characteristics	Performance
Capacity of flushing water (CF)	Confirmed
Backflow prevention (BP)	Confirmed
Cleanability (CA)	Confirmed
Load resistance (LR)	Confirmed
Water-, leaktightness (WT)	Confirmed
Valve reliability (VR)	Confirmed
Durability (DA)	Confirmed

The declared performance of the product is shown in the essential characteristics and in the designation code of the attached list.

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer



Joan Pedro Santos
Manufacturing Manager

DoP no 997

Matching flushing cistern	Average water consumption	Designation code
LAUFEN LIS 894665	3,50	EN 16578 - S5
LAUFEN LIS 894665	3,50	EN 16578 - S5
LAUFEN LIS 89466x	7,00	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,73	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
LAUFEN LIS 894665	3,50	EN 16578 - S5
LAUFEN LIS 89466x	3,73	EN 16578 - S5
LAUFEN LIS 894665	3,50	EN 16578 - S5
LAUFEN LIS 89466x	3,73	EN 16578 - S5
	3,50	EN 16578 - S5
	3,73	EN 16578 - S5
	3,50	EN 16578 - S5
	3,73	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,73	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,73	EN 16578 - S5
	3,75	EN 16578 - S5
	3,73	EN 16578 - S5
	3,75	EN 16578 - S5
	3,73	EN 16578 - S5
	3,75	EN 16578 - S5
	3,73	EN 16578 - S5
	3,75	EN 16578 - S5
	3,73	EN 16578 - S5
	3,75	EN 16578 - S5
	3,73	EN 16578 - S5
	3,75	EN 16578 - S5
	3,73	EN 16578 - S5
	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5

Sub

P = Pack

DECLARATION OF PERFORMANCE

DoP no 997

Product No.		Name	Product type	Matching flushing cistern	Designation code	Essential characteristics	min. volume
H821372		Lyra new	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H824276	H824236	Lyra new/Concept	PCS	2827.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824276	H826398	Lyra new/Troma	PCS	2664.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824276	H860270	Lyra new/Easy/Norma	PCS	2664.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824276	H860272	Lyra new/Euroline	PCS	2827.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824276	H860274	Lyra new/RPG	PCS	2634.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824276	H861640	Lyra new	PCS	2827.2,3	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824276	H824178	Lyra new/Uni	PCS	2797.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824277	H825237	Lyra new	PCS	2827.2,3	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824277	H824237	Lyra new/Concept	PCS	2827.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824277	H826399	Lyra new/Troma	PCS	2664.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824277	H860271	Lyra new/Easy/Norma	PCS	2664.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824277	H860273	Lyra new/Euroline	PCS	2827.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824277	H860275	Lyra new/RPG	PCS	2634.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824277	H824179	Lyra new/Uni	PCS	2797.2	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H821386		Lyra plus	PP		EN 997 - CL1 - 5A	CF - BP - CA - DA	5/3
H821387		Lyra plus	PP		EN 997 - CL1 - 5A	CF - BP - CA - DA	5/3
H823380	H823261	Lyra plus	WP		EN 997 - CL1 - 6A - 6C	CF - BP - CA - LR - DA	6/3
H823380	H862383	Lyra plus	WP		EN 997 - CL1 - 6A - 6C	CF - BP - CA - LR - DA	6/3
H823380	H823261	Lyra plus	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H823380	H862383	Lyra plus	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H823382	H860382	Lyra plus	WP		EN 997 - CL1 - 6A - 6C	CF - BP - CA - LR - DA	6/3
H823382	H860382	Lyra plus	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H824384	H826384	Lyra plus	PCS	2838.2,3	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824386	H826386	Lyra plus	PCS	2838.2,3	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824386	H862386	Lyra plus	PCS	2838.2,3	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824387	H826387	Lyra plus	PCS	2838.2,3	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824387	H862387	Lyra plus	PCS	2838.2,3	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H825386		Lyra plus	PP		EN 997 - CL1 - 6A - 6C	CF - BP - CA - DA	6/3
H825387		Lyra plus	PP		EN 997 - CL1 - 6A - 6C	CF - BP - CA - DA	6/3
H820712		Mio	WP		EN 997 - CL1 - 6/5A - 6C	CF - BP - CA - LR - DA	6/3
H820712		Mio	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H820714		Mio rimless	WP		EN 997 - CL1 - 5A	CF - BP - CA - LR - DA	5/3
H820714		Mio rimless	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H823716		Mio	PCS	2771.2,3, 2871.7	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H823716		Mio	PCS	2771.2,3, 2871.7	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H824716	H824718	Mio	PCS	2771.2,3, 2871.7	EN 997 - CL1 - 6 - VR II	CF - BP - CA - LR - DA	6/3
H824716	H824718	Mio	PCS	2771.2,3, 2871.7	EN 997 - CL2 - 5,9	CF - BP - CA - DA - WT - VR	5,9/3
H820228		Prisma	WP		EN 997 - CL1 - 6A	CF - BP - CA - LR - DA	6/3
H820423		Pure	WP		EN 997 - CL1 - 5A - 6C	CF - BP - CA - LR - DA	6/3
H820423		Pure	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9/3
H823424		Pure	PP		EN 997 - CL1 - 5A - 6C	CF - BP - CA - DA	6/3
H823424		Pure	PP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - DA	5,9/3
H824426		Pure	PCS	2842.2,3	EN 997 - CL1 - 5 - VR II	CF - BP - CA - LR - DA	5/3

**EUROPEAN WATER
LABEL**

Matching flushing cistern	Average water consumption
LAUFEN LIS 89466x	3.75
	3.75
	3.75
	3.75
	3.75
	3.75
	3.75
	3.75
	3.75
	3.75
	3.75
	3.75
LAUFEN LIS 894665	3.50
LAUFEN LIS 894665	3.50
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
	3.75
	3.75
	3.75
	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 894665	3.50
LAUFEN LIS 89466x	3.75
	3.75
	3.75
	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
LAUFEN LIS 89466x	3.75
	3.50

SUSTAINABILITY ASSESSMENT

[illegible]

Signed for and on behalf of the manufacturer

P = Pack

LAUFEN CZ, spol. s r. o.
The Czech Republic, 18.10.2018

page: 3/4


Joan Pedro Santos
Manufacturing Manager

DECLARATION OF PERFORMANCE

DoP no 997

Product No.		Name	Product type	Matching flushing cistern	Designation code	Essential characteristics	min. volume
H824426		Pure	PCS	2842.2,3	EN 997 - CL2 - 5,9	CF - BP - CA - DA - WT - VR	5,9
H821156		Roman	PP		EN 997 - CL1 - 9A	CF - BP - CA - DA	
H821157	H821217	Roman	PP		EN 997 - CL1 - 9A	CF - BP - CA - DA	
H821227		Sam	PP		EN 997 - CL1 - 6A	CF - BP - CA - DA	6
H822386	H826286	Scandia	PCS	2828.3, 2938.5	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H822386	H824286	Scandia	PCS	2828.3, 2938.5	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H825287	H826287	Scandia	PCS	2828.3	EN 997 - CL1 - 6 - 4 - VRII	CF - BP - CA - LR - DA	6
H825288	H826289	Scandia	PCS	2828.3	EN 997 - CL1 - 6 - 4 - VRII	CF - BP - CA - LR - DA	6
H820213		Tigo	WP		EN 997 - CL1 - 5A - 6C	CF - BP - CA - LR - DA	5
H820213		Tigo	WP	LAUFEN LIS 89466x	EN 997 - CL2 - 5,9	CF - BP - CA - LR - DA - WT - VR	5,9
H824216		Tigo	PCS	2821.2,3	EN 997 - CL1 - 5 - VRII	CF - BP - CA - DA - WT - VR	5
H824216		Tigo	PCS	2821.2,3	EN 997 - CL2 - 5,9	CF - BP - CA - LR - WL - VR - DA	5,9
H821390		Troma	WP		EN 997 - CL1 - 6A - 6C	CF - BP - CA - LR - DA	6
H820396	H860396	Zeta	WP		EN 997 - CL1 - 6A	CF - BP - CA - LR - DA	6
H822396		Zeta	PP		EN 997 - CL1 - 6A - 6C	CF - BP - CA - DA	6
H822397		Zeta	PP		EN 997 - CL1 - 6A	CF - BP - CA - DA	6
H824396	H860100	Zeta	PCS	2839.2,3, 2827.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824396	H825396	Zeta	PCS	2839.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824396	H825496	Zeta	PCS	2839.2,3, 2827.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824396	H861393	Zeta/Neo	PCS	2761.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824396	H861390	Zeta/Neo	PCS	2839.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824396	H860276	Zeta/Diana	PCS	2839.2,3, 2827.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824397	H825497	Zeta	PCS	2839.2,3, 2827.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824397	H860101	Zeta	PCS	2839.2,3, 2827.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824397	H825397	Zeta	PCS	2839.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824397	H861395	Zeta/Neo	PCS	2761.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824397	H861399	Zeta/Neo	PCS	2839.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824397	H860277	Zeta/Diana	PCS	2839.2,3, 2827.2	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H824286		Baltic	PCS	2828.3	EN 997 - CL1 - 6 - VRII	CF - BP - CA - LR - DA	6
H826282		Lyra plus Scandia	PCS	2938.5	EN 997 CL1-6-4-VRII	CF - BP - CA - LR - DA	6
H826283		Lyra plus Scandia	PCS	2938.5	EN 997 CL1-6-4-VRII	CF - BP - CA - LR - DA	6
H821746		Munike	PP		EN 997 CL1 - 6A -6C	CF - BP - CA - DA	6
H821747		Munike	PP		EN 997 CL1 - 6A -6C	CF - BP - CA - DA	6
A342ND0000	H826383	Lyra plus Scandia	PCS	2838.0	EN 997 CL1-6-4-VRII	CF - BP - CA - LR - DA	6
A342ND1000	H826389	Lyra plus Scandia	PCS	2838.0	EN 997 CL1-6-4-VRII	CF - BP - CA - LR - DA	6

**EUROPEAN WATER
LABEL**

SUSTAINABILITY ASSESSMENT


Matching flushing cistern	Average water consumption	Designation code
	3,73	EN 16578 - S5
LAUFEN LIS 89466x	9,00	EN 16578 - S5
LAUFEN LIS 89466x	9,00	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
LAUFEN LIS 894665	3,50	EN 16578 - S5
LAUFEN LIS 89466x	3,73	EN 16578 - S5
	3,50	EN 16578 - S5
	3,73	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
LAUFEN LIS 89466x	3,75	EN 16578 - S5
	3,75	EN 16578 - S5
	3,75	EN 16578 - S5

P = Pack

LAUFEN CZ, spol. s r. o.
The Czech Republic, 18.10.2018

page: 4/4

Signed for and on behalf of the manufacturer


Joan Pedro Santos
Manufacturing Manager